

UTILITY  
PATENT APPLICATION  
TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket  
No.

PVC-P-99-002

First Named Inventor or Application Identifier

Maximilian Luttrell

Express Mail Label No. EL 613928501 US

ADDRESS TO: Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Specification Total Pages 21
2. ☒ Drawing(s) (35USC 113) Total Pages 01
3. ☒ Declaration and Power of Attorney Total Pages 02
- a. ☒ Newly executed (OR FAXED COPY)
- b. ☐ Copy from prior application (37CFR 1.63(d))  
(for continuation/divisional with Box 14 completed)  
[Note Box 4 Below]
- i. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting  
inventor(s) named in the prior application,  
see 37 CFR 1.63(d)(2) and 1.33(b).
4. ☐ Incorporation By Reference (usable if Box 3b is checked)  
The entire disclosure of the prior application, from which a  
copy of the oath or declaration is supplied under Box 3b,  
is considered as being part of the disclosure of the  
accompanying application and is hereby incorporated by  
reference therein.

ACCOMPANYING APPLICATION PARTS

5. ☒ Assignment Papers (cover sheet & documentation)  
including check for \$40.00 recordation fee
6. ☐ Letter under 37 CFR 1.41(c).
7. ☐ English Translation Document (if applicable)
8. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
9. ☐ Preliminary Amendment
10. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
11. ☒ Small Entity ☐ Statement filed in prior application,  
Statement(s) Status still proper and desired
12. ☐ Certified Copy of Priority Document(s)
13. ☐ Other:

14. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) ☐ of prior application No: \_\_\_\_\_

CLAIMS AS FILED

CLAIMS AS FILED				
(1) NUMBER OF CLAIMS ALLOWED	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) BASIC FEE (Small Entity) \$345.00
TOTAL CLAIMS 20	19	0	9.00	0
INDEPENDENT CLAIMS 03	02	0	39.00	0
	ANY MULTIPLE DEPENDENT CLAIMS? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		260.00	0
			TOTAL FILING FEE ->	\$345.00

- ☒ The Commissioner is hereby authorized to charge any additional fees which may be required in connection with this application, or credit any overpayment to DEPOSIT ACCOUNT NO. 50-0595. A duplicate copy of this sheet is enclosed.
- ☒ A check in the amount of \$ 345.00 to cover the filing fee is enclosed.

15. CORRESPONDENCE ADDRESS

PATENTS+TMS  
A Professional Corporation  
1914 North Milwaukee Avenue  
Chicago, Illinois 60647  
Telephone (773) 772-6009 - Fax (773) 772-3210

SIGNATURE:

Brian M. Mattson (Reg. No. 35,018)

DATE:

July 12, 2000

Attorney's

Applicant(s) or Patentee(s) Maximilian Luttrell et al. Docket No.: PVC-P-99-002  
 Serial or Patent No. \_\_\_\_\_  
 Filed or Issued: \_\_\_\_\_ For: "METHOD  
AND SYSTEM FOR EMBEDDING BINARY DATA SEQUENCES INTO VIDEO BITSTREAMS"

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS**  
**(37 CFR 1.9(f) & 1.27(c)) - SMALL BUSINESS CONCERN**

I hereby declare that I am

- ☐ the owner of the small business concern identified below:  
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN PackerVideo Corporation  
 ADDRESS OF CONCERN 10350 Science Center Drive, Suite 140, San Diego, CA 92121

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 CFR 121.12, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention entitled: "METHOD AND SYSTEM FOR EMBEDDING BINARY DATA SEQUENCES INTO VIDEO BITSTREAMS" by inventor(s) Luttrell et al. as described in

- ☒ the specification filed herewith  
☐ application Serial No. \_\_\_\_\_, filed \_\_\_\_\_  
☐ Patent No. \_\_\_\_\_, issued \_\_\_\_\_

If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e). NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27).

NAME  
 ADDRESS

- ☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date and which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING Joel E. Espelien  
 TITLE OF PERSON OTHER THAN OWNER Vice President of Legal Affairs  
 ADDRESS OF PERSON SIGNING c/o PackerVideo Corporation, 10350 Science Center Drive, Suite 140, San Diego, CA 92121

SIGNATURE Joel E. Espelien DATE 7-11-2000

006443-01000

## VIDEO BITSTREAMS"

## BACKGROUND OF THE INVENTION

The present invention generally relates to a method and a system for embedding binary data sequences into video bitstreams which may be utilized in a Digital Rights Management (DRM) system. Further, the present invention relates to a method and a system for embedding binary data into compressed standard compliant video bitstreams without having to first decompress the video bitstream and then re-compress the manipulated video sequence with data embedded. The present invention is especially suitable for bitstreaming to set-top boxes, wireless telephones, handheld devices, multimedia servers or gateways, where the computational and memory requirements for real-time compression of video materials is prohibitively expensive. In accordance with the present invention, the embedded data can be any binary data sequence. In particular, it may be utilized in a Digital Rights Management system for authentication and access control purposes, such as, for example, access control, creating signatures, watermarking, and/or in-band signaling.

Demands for full motion video in such applications as video telephony, video conferencing, and/or multimedia applications have required the introduction of standards for motion video on computers and related systems. Such applications have further required development of compression techniques that can reduce the amount of data required to represent a moving image and corresponding sound to manageable lengths to, for example, facilitate data transmission using conventional communications equipment with limited transmission capabilities.

One set of standards for compression of motion picture video images for transmission or storage is known as the Motion Picture

Two versions of the MPEG video standard which have received widespread adoption are commonly known as the MPEG-1 and MPEG-2 standards. In general, the MPEG-2 standard has higher resolution and quality than the MPEG-1 standard and enables broadcast transmission at a rate of 4-6 Mbps. In addition to the MPEG-1 and MPEG-2 standards, the MPEG-4 standard is now standardized by the International Organization of Standardization ("ISO") and the International Electrotechnical Commission ("IEC"). The MPEG-4 standard is intended to facilitate, for example, content-based interactivity and certain wireless applications.

The video codes specified by the MPEG and ITU standards are very similar and provide compression of a digital video sequence by utilizing a block motion-compensated Discrete Cosine Transform ("DCT"). In a first block matching step of the DCT process, an algorithm estimates and compensates for the motion that occurs between two temporally adjacent frames. The frames are then compensated for the estimated motion and compared to form a difference image. By taking the difference between the two temporally adjacent frames, all existing temporal redundancy is removed. The only information that remains is new information

In a second step, this new information is transformed into the frequency domain using the DCT. The DCT has the property of compacting the energy of this new information into a few low frequency components. Further compression of the video sequence is obtained by limiting the amount of high frequency information encoded through quantization and entropy coding of information after quantization.

Utilizing the estimated motion vectors, a copy of the previous frame may be altered by each vector to produce a prediction of the current frame. This operation is referred to as motion compensation. As described above, each predicted MB may be subtracted from the current MB to produce a differential MB whose four blocks are transformed independently into the frequency domain by the DCT. These coefficients are quantized and entropy encoded using variable length codes ("VLCs") to provide further compression of the original video sequence. Both the motion vectors and the DCT coefficients are transmitted to the decoder wherein an inverse operation is performed to produce the decoded video sequence.

MBs coded with the above described process are called

For both INTER and INTRA MBs, many of the DCT coefficients are zero after quantization. Therefore, to achieve better entropy coding efficiency, the VLC codes are not coded with quantized coefficients themselves, but are coded with the non-zero coefficients and the number of consecutive zero coefficients between them. More specifically, before entropy compression coding of run-length coded quantized DCT coefficients, the DCT coefficients in an 8 x 8 block are mapped to EVENTS which are triplets of the form  $EVENT = (RUN, LEVEL, LAST)$ , where RUN designates the number of consecutive DCT coefficients that are quantized to zero since the last non-zero DCT coefficient; LEVEL designates the amplitude and the sign of the current non-zero coefficient; and LAST designates whether the current non-zero coefficient is the last non-zero coefficient in the block. All EVENTS generated by non-zero coefficients in an 8 x 8 block have  $LAST = 0$  except for the last EVENT in a block for which  $LAST = 1$ .

As computers and computer networks become faster and more

An additional concern of DRM techniques or systems is the issue of error resiliency when DRM systems are deployed in wireless networks. Wireless networks often suffer from packet loss and/or biterrors to data during data transmission. As a result, to deliver content over wireless channels, in a manner that preserves the utility of the DRM system, it is necessary for the DRM system to be error resilient. Unfortunately, security and error resiliency have contradictory requirements. A good encryption scheme has to be a good randomizer, while redundancy is needed to achieve resiliency. One existing error resilient DRM scheme involves channel coding. Channel coding consists of

A need, therefore, exists for an improved error resilient DRM method and system for providing authentication and access control in video delivery over wireless networks.

The present invention provides a method and a system for embedding binary bits into a standard compliant compressed video bitstream for use in DRM systems and other systems. Further, the present invention provides a method and a system for embedding binary bits without having to decode and subsequently re-encode the original video bitstream.

In an embodiment, the bitstream is scanned to find spatial locations for embedding data bits.

In an embodiment, a system is provided for embedding information into a digitally compressed bitstream. The system has a compressed bitstream, a means for identifying locations in the compressed bitstream, and a means for replacing original codewords in the bitstream with alternate codewords.

In an embodiment, a means is provided for scanning the bitstream to locate INTER or INTRA blocks (hereinafter, the



"blocks") wherein the blocks contain the original codewords.

In an embodiment, the bitstream has final codewords and further wherein the locations in the bitstream for embedding data into the bitstream correspond to the final codewords in the bitstream.

In an embodiment, the blocks have a last non-zero coefficient having an index number of less than 63.

In an embodiment, the codewords have a triplet form of EVENT = (RUN, LEVEL, LAST) and further wherein the final codewords in the bitstream have "LAST" coefficients = 1.

In an embodiment, a means is provided for replacing final codewords in the bitstream with replaced codewords wherein the replaced codewords have LAST coefficients = 0.

In an embodiment, a means is provided for appending alternate codewords to the replaced codewords wherein the alternate codewords = "0111s" wherein the "s" represents the embedded data bit.

In an embodiment, the compressed bitstream corresponds to a compressed video bitstream.

It is, therefore, an advantage of the present invention to provide a method and a system that embeds binary bits into a compressed video bitstream.

A further advantage of the present invention is to provide a method and a system for embedding binary bits into a compressed video bitstream without decoding and subsequently re-encoding the bitstream.

Moreover, an advantage of the present invention is to provide a method and a system for embedding binary bits into a compressed video bitstream that parses the compressed video bitstream and searches for the blocks.

A still further advantage of the present invention is to provide a method and a system for embedding binary bits into a compressed video bitstream that replaces the last triplet in the

blocks with an embedded data bit.

In addition, an advantage of the present invention is to provide a method and a system for embedding binary bits into a compressed video bitstream where a code word in the video bitstream is replaced with an alternate code word having the embedded data bit.

A still further advantage of the present invention is to provide a method and a system for embedding binary bits into a compressed video bitstream that is suitable for devices where memory and/or computational power resources are limited.

Additional features and advantages of the present invention are described in, and will be apparent from, the detailed description of the presently preferred embodiments and from the drawings.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 illustrates a black box diagram of a system in an embodiment of the present invention.

## DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

The present invention provides a method and a system for embedding binary bits into a compressed video bitstream. Further, the present invention relates to a digital rights management method and system for embedding binary bits into a standard video bitstream without having to decode and/or subsequently re-encode the original video bitstream.

Referring to Figure 1, a flowchart presents a method of embedding data into a compressed bitstream for authentication purposes. According to the method, blocks are located in the original pre-compressed bitstream. For each block which is located, the codeword  $C = (RUN_C, LEVEL_C, LAST_C = 1)$  for the last triplet in the original bitstream may be replaced with a VLC

codeword  $C' = (RUN_c, LEVEL_c, LAST_c = 0)$ , and a codeword corresponding to a triplet with  $LEVEL = 1$  and  $LAST = 1$  is placed after  $C'$ , whose sign bit "s" is either 0 or 1 and is an embedded data bit. With reference to Tables 1 and 2, the codewords in the tables issued for the most commonly occurring EVENTS for the luminance and chrominance components of INTRA and INTER blocks wherein  $EVENT = (RUN, LEVEL, LAST)$ . The last bit "s" of each VLC code denotes the sign of the LEVEL: "0" for positive and "1" for negative. The remaining combinations of  $EVENT = (RUN, LEVEL, LAST)$  are coded with the escape code in the tables, followed by a 23-bit fixed length code ("FLC") for a total of 30 bits. The FLC starts with the 2-bit pattern "11" which is followed by a 1-bit LAST flag, a 6-bit RUN, and a 12-bit LEVEL with a marker bit before and after the LEVEL bits.

TAB - 1 -- VLC Table for Intra Luminance and Chrominance TCOEF

VLC Code	LAST	RUN	LEVEL	VLC Code	LAST	RUN	LEVEL
10s	0	0	1	0111 s	1	0	1
1111 s	0	0	3	0000 1100 1s	0	11	1
0101 01s	0	0	6	0000 0000 101s	1	0	6
0010 111s	0	0	9	0011 11s	1	1	1
0001 1111 s	0	0	10	0000 0000 100s	1	0	7
0001 0010 1s	0	0	13	0011 10s	1	2	1
0001 0010 0s	0	0	14	0011 01s	0	5	1
0000 1000 01s	0	0	17	0011 00s	1	0	2
0000 1000 00s	0	0	18	0010 011s	1	5	1
0000 0000 111s	0	0	21	0010 010s	0	6	1
0000 0000 110s	0	0	22	0010 001s	1	3	1
0000 0100 000s	0	0	23	0010 000s	1	4	1
110s	0	0	2	0001 1010 s	1	9	1
0101 00s	0	1	2	0001 1001 s	0	8	1
0001 1110 s	0	0	11	0001 1000 s	0	9	1
0000 0011 11s	0	0	19	0001 0111 s	0	10	1
0000 0100 001s	0	0	24	0001 0110 s	1	0	3
0000 0101 0000s	0	0	25	0001 0101 s	1	6	1
1110 s	0	1	1	0001 0100 s	1	7	1
0001 1101 s	0	0	12	0001 0011 s	1	8	1
0000 0011 10s	0	0	20	0000 1100 0s	0	12	1
0000 0101 0001s	0	0	26	0000 1011 1s	1	0	4

0110 1s	0	0	4
0001 0001 1s	0	0	15
0000 0011 01s	0	1	7
0110 0s	0	0	5
0001 0001 0s	0	4	2
0000 0101 0010s	0	0	27
0101 1s	0	2	1
0000 0011 00s	0	2	4
0000 0101 0011s	0	1	9
0100 11s	0	0	7
0000 0010 11s	0	3	4
0000 0101 0100s	0	6	3
0100 10s	0	0	8
0000 0010 10s	0	4	3
0100 01s	0	3	1
0000 0010 01s	0	8	2
0100 00s	0	4	1
0000 0010 00s	0	5	3
0010 110s	0	1	3
0000 0101 0101s	0	1	10
0010 101s	0	2	2
0010 100s	0	7	1
0001 1100 s	0	1	4
0001 1011 s	0	3	2
0001 0000 1s	0	0	16
0001 0000 0s	0	1	5
0000 1111 1s	0	1	6
0000 1111 0s	0	2	3
0000 1110 1s	0	3	3
0000 1110 0s	0	5	2
0000 1101 1s	0	6	2
0000 1101 0s	0	7	2
0000 0100 010s	0	1	8
0000 0100 011s	0	9	2
0000 0101 0110s	0	2	5
0000 0101 0111s	0	7	3

0000 1011 0s	1	1	2
0000 1010 1s	1	10	1
0000 1010 0s	1	11	1
0000 1001 1s	1	12	1
0000 1001 0s	1	13	1
0000 1000 1s	1	14	1
0000 0001 11s	0	13	1
0000 0001 10s	1	0	5
0000 0001 01s	1	1	3
0000 0001 00s	1	2	2
0000 0100 100s	1	3	2
0000 0100 101s	1	4	2
0000 0100 110s	1	15	1
0000 0100 111s	1	16	1
0000 0101 1000s	0	14	1
0000 0101 1001s	1	0	8
0000 0101 1010s	1	5	2
0000 0101 1011s	1	6	2
0000 0101 1100s	1	17	1
0000 0101 1101s	1	18	1
0000 0101 1110s	1	19	1
0000 0101 1111s	1	20	1
0000 011	escape		

TAB - 2 – VLC table for Inter Luminance and Chrominance TCOEF

VLC Code	LAST	RUN	LEVEL
10s	0	0	1
1111 s	0	0	2
0101 01s	0	0	3

VLC Code	LAST	RUN	LEVEL
0111 s	1	0	1
0000 1100 1s	1	0	2
0000 0000 101s	1	0	3

0000 0101 0000

0010 111s	0	0	4
0001 1111 s	0	0	5
0001 0010 1s	0	0	6
0001 0010 0s	0	0	7
0000 1000 01s	0	0	8
0000 1000 00s	0	0	9
0000 0000 111s	0	0	10
0000 0000 110s	0	0	11
0000 0100 000s	0	0	12
110s	0	1	1
0101 00s	0	1	2
0001 1110 s	0	1	3
0000 0011 11s	0	1	4
0000 0100 001s	0	1	5
0000 0101 0000s	0	1	6
1110 s	0	2	1
0001 1101 s	0	2	2
0000 0011 10s	0	2	3
0000 0101 0001s	0	2	4
0110 1s	0	3	1
0001 0001 1s	0	3	2
0000 0011 01s	0	3	3
0110 0s	0	4	1
0001 0001 0s	0	4	2
0000 0101 0010s	0	4	3
0101 1s	0	5	1
0000 0011 00s	0	5	2
0000 0101 0011s	0	5	3
0100 11s	0	6	1
0000 0010 11s	0	6	2
0000 0101 0100s	0	6	3
0100 10s	0	7	1
0000 0010 10s	0	7	2
0100 01s	0	8	1
0000 0010 01s	0	8	2
0100 00s	0	9	1
0000 0010 00s	0	9	2
0010 110s	0	10	1
0000 0101 0101s	0	10	2
0010 101s	0	11	1
0010 100s	0	12	1
0001 1100 s	0	13	1
0001 1011 s	0	14	1
0001 0000 1s	0	15	1

0011 11s	1	1	1
0000 0000 100s	1	1	2
0011 10s	1	2	1
0011 01s	1	3	1
0011 00s	1	4	1
0010 011s	1	5	1
0010 010s	1	6	1
0010 001s	1	7	1
0010 000s	1	8	1
0001 1010 s	1	9	1
0001 1001 s	1	10	1
0001 1000 s	1	11	1
0001 0111 s	1	12	1
0001 0110 s	1	13	1
0001 0101 s	1	14	1
0001 0100 s	1	15	1
0001 0011 s	1	16	1
0000 1100 0s	1	17	1
0000 1011 1s	1	18	1
0000 1011 0s	1	19	1
0000 1010 1s	1	20	1
0000 1010 0s	1	21	1
0000 1001 1s	1	22	1
0000 1001 0s	1	23	1
0000 1000 1s	1	24	1
0000 0001 11s	1	25	1
0000 0001 10s	1	26	1
0000 0001 01s	1	27	1
0000 0001 00s	1	28	1
0000 0100 100s	1	29	1
0000 0100 101s	1	30	1
0000 0100 110s	1	31	1
0000 0100 111s	1	32	1
0000 0101 1000s	1	33	1
0000 0101 1001s	1	34	1
0000 0101 1010s	1	35	1
0000 0101 1011s	1	36	1
0000 0101 1100s	1	37	1
0000 0101 1101s	1	38	1
0000 0101 1110s	1	39	1
0000 0101 1111s	1	40	1
0000 011	escape		

0001 0000 0s	0	16	1
0000 1111 1s	0	17	1
0000 1111 0s	0	18	1
0000 1110 1s	0	19	1
0000 1110 0s	0	20	1
0000 1101 1s	0	21	1
0000 1101 0s	0	22	1
0000 0100 010s	0	23	1
0000 0100 011s	0	24	1
0000 0101 0110s	0	25	1
0000 0101 0111s	0	26	1

In Table 3, all VLC codewords for EVENTS with LAST = 1 from Table 1 are listed, and, in each row, the codeword for the EVENT with the same RUN and LEVEL, but with LAST = 0, is also given. The EVENTS with LAST = 1 that need to be coded with the FLC are not listed because the same code length is used for the EVENTS with LAST = 0. According to Table 3, the codeword for the EVENT with LAST = 1 is generally longer than for the corresponding EVENT in the same row with LAST = 0.

TAB - 3

Difference between LAST=0 and LAST=1 VLCs for INTRA macroblock DCT TCOEF

RUN	LEVEL	VLC Code		Len Diff.
		LAST = 1	LAST = 0	
0	1	0111 s	10s	2
1	1	0011 11s	1110 s	2
2	1	0011 10s	0101 1s	1
0	2	0011 00s	110s	3
5	1	0010 011s	0011 01s	1
3	1	0010 001s	0100 01s	1
4	1	0010 000s	0100 00s	1
9	1	0001 1010 s	0001 1000 s	0
0	3	0001 0110 s	1111 s	4
6	1	0001 0101 s	0010 010s	1

7	1	0001 0100 s	0010 100s	1
8	1	0001 0011 s	0001 1001 s	0
0	4	0000 1011 1s	0110 1s	4
1	2	0000 1011 0s	0101 00s	3
10	1	0000 1010 1s	0001 0111 s	1
11	1	0000 1010 0s	0000 1100 1s	0
12	1	0000 1001 1s	0000 1100 0s	0
13	1	0000 1001 0s	0000 0001 11s	-1
14	1	0000 1000 1s	0000 0101 1000 s	-3
0	5	0000 0001 10s	0110 0s	5
1	3	0000 0001 10s	0010 110s	3
2	2	0000 0001 00s	0010 101s	3
0	6	0000 0000 101s	0101 01s	5
3	2	0000 0100 100s	0001 1011 s	3
0	7	0000 0000 100s	0100 11s	5
4	2	0000 0100 101s	0001 0001 0s	2
15	1	0000 0100 110s	FLC (30 bits)	-18
16	1	0000 0100 111s	FLC (30 bits)	-18
0	8	0000 0101 1001 s	0100 10s	6
5	2	0000 0101 1010 s	0000 1110 0s	3
6	2	0000 0101 1011 s	0000 1101 1s	3
17	1	0000 0101 1100 s	FLC (30 bits)	-17
18	1	0000 0101 1101 s	FLC (30 bits)	-17
19	1	0000 0101 1110 s	FLC (30 bits)	-17
20	1	0000 0101 1111 s	FLC (30 bits)	-17

Therefore, the video bitstream may be parsed to get the MB type (INTER or INTRA) information to embed data into compressed video bitstreams. For each block, the last codeword for DCT information may be found. By definition of LAST, this codeword C corresponds to an EVENT = (RUN<sub>C</sub>, LEVEL<sub>C</sub>, LAST<sub>C</sub>) with LAST<sub>C</sub> = 1. In other words, the codeword C is removed from the bitstream and replaced with the codeword for the EVENT = (RUN<sub>C</sub>, LEVEL<sub>C</sub>, LAST<sub>C</sub>' = 0). The codeword "0111S" is then be used to terminated the block.

Although the present method embeds five bits to the end of each block for every one data bit embedded, the overhead introduced by the above-described method is relatively small. As shown in Table 3, most EVENTS with LAST = 1 have a longer code length than the EVENT with the same RUN and LEVEL but with LAST = 0. Most times, after appending the amended codeword, a total extra overhead of less than five bits is produced. Accordingly, Table 4 shows the length overhead in bits after the proposed manipulation of the bitstream for a plurality of various EVENTS at various RUN and LEVEL values.

**TAB - 4**  
**Length Overhead After Proposed Embedding Operation**

RUN	LEVEL	Length Overhead after Proposed Operation
0	1	3
1	1	3
2	1	4
0	2	2
5	1	4
3	1	4
4	1	4
9	1	5
0	3	1
6	1	4
7	1	4
8	1	5
0	4	1
1	2	2
10	1	4
11	1	5
12	1	5
13	1	6
14	1	8
0	5	0

002240" T 2547960



1	3	2
2	2	2
0	6	0
3	2	2
0	7	0
4	2	3
15	1	23
16	1	23
0	6	-1
5	2	2
6	2	2
17	1	22
18	1	22
19	1	22
20	1	22

The additional codeword appended to the end of an block corresponds to inserting a frequency that was not actually present in the sequence, and, therefore, introduces some noise. However, because the appended codeword may be inserted after the non-zero DCT coefficient of the highest spatial frequency present in the block, the introduced noise may likely be of a high spatial frequency. Further, because the codeword for embedding corresponds to an EVENT of LEVEL = 1, the introduced noise may likely be small. Overall, the visual effect of this data-embedding method may be designed to be based on image content analysis, scene change detection, characteristics of the human visual systems and/or other like systems that may be apparent to those skilled in the art to pick appropriate blocks to apply this data-embedding method.

It should be noted that, because there can be at most 64 non-zero coefficients in a block, for blocks whose original last non-zero DCT coefficient is the 64<sup>th</sup> coefficient, the above described manipulation is impossible. In addition, if

the original last non-zero DCT coefficient is the 64<sup>th</sup> coefficient, and the above-described method is performed, it will become ambiguous to the decoder if the last codeword "0111s" is added to the amended codeword. Therefore, in an embodiment it is useful to circumvent these problems, and the codeword replacement and the adding of the appended codeword may therefore be done only when the last non-zero coefficient has an index number smaller than 63. Then, if the decoder that attempts to extract data from a data-embedded bitstream finds the LAST = 1 for the 64<sup>th</sup> coefficient, that LEVEL must be a "true" DCT coefficient.

Using the above, the flowchart, as shown in Figure 1, shows the method of embedding data into bitstreams for authentication purposes. According to Figure 1, certain bits from the original bitstream (shown as bits from an MPEG 4 frame 52, however, other types of bitstreams may be used) are extracted from the bitstream. The bits 52 are then passed through a public key encryption device via an encryption step 56 via a sender's private key 54 thereby producing encrypted bits 58. An embedding mechanism 60 then embeds the encrypted bits 58 into the bitstream thereby producing a watermarked MPEG 4 frame 61.

A receiver, after receiving the bitstream extracts the embedded information 64 using an extraction mechanism 62. The extracted encrypted bits 64 then decrypts via the decryption step 66. The encrypted bits 64 are decrypted using a public key 68 which may be published. The decrypted bits 70 are then checked against the original frame data via step 72. If the original bits from the MPEG 4 frame 52 and the decrypted bits 70 are the same, then the bitstream may be authentic as shown in step 74. Alternatively, if the original bits from the MPEG 4 frame 52 are not the same as the decrypted bits 70 via step 76, then the bitstream has been tampered with.

Using the above-identified method via the flowchart 50, the method and the sender's public key may be published. The private key 54 remains secure.

Although the above application has been described primarily in the context of adding a specific codeword (i.e. "0111s") to the DCT information of blocks in an MPEG or H.263 compliant compressed video bitstreams, one skilled in the art can readily appreciate that the teachings of the present invention may be modified to append other codewords to possibly other types of MBs or to selectively choose locations for data embedding based on an algorithm that the embedded data extracting decoder can easily access.

It should be understood that various changes and modifications to the presently preferred embodiments described herein will be apparent to those skilled in the art. Such changes and modifications may be made without departing from the spirit and scope of the present invention and without diminishing its attendant advantages. It is, therefore, intended that such changes and modifications be covered by the appended claims.

003720"074600

**What is claimed is:**

1. A method for embedding information into a digitally compressed bitstream, the method comprising the steps of:  
    providing a compressed bitstream;  
    identifying locations in the bitstream for embedding data into the bitstream; and  
    replacing original codewords in the bitstream with alternate codewords having embedded data bits.
2. The method of Claim 1 further comprising the step of:  
    scanning the bitstream to find spatial locations for embedding data bits.
3. The method of Claim 1 further comprising the step of:  
    scanning the bitstream to find temporal locations for embedding data bits.
4. The method of Claim 1 further comprising the step of:  
    scanning the bitstream to find spatial or temporal locations for embedding data bits that can be reliably recovered by an error resilience decoder if the bitstream is subjected to errors during transmission.
5. The method of Claim 1 further comprising the step of:  
    finding blocks wherein the blocks have a last non-zero coefficient having an index number of less than 63.
6. The method of Claim 1 wherein the original codewords have a triplet form of EVENT = (RUN, LEVEL, LAST) and further wherein final codewords in the bitstream have a "LAST" coefficient = 1.

002441-07400

7. The method of Claim 6 further comprising the step of:  
replacing the final codewords so that the final codewords have a "LAST" coefficient = 0.
8. The method of Claim 6 further comprising the step of:  
appending alternate codewords to the final codewords in the bitstream.
9. The method of Claim 8 wherein the alternate codewords = "0111s" wherein the "s" corresponds to the embedded data bit.
10. The method of Claim 1 wherein the bitstream is compliant with international standards.
11. The method of Claim 1 wherein the bitstream is a video bitstream.
12. A system for embedding information into a digitally compressed bitstream, the system comprising:  
a compressed bitstream;  
means for identifying locations in the compressed bitstream; and  
means for replacing original codewords in the bitstream with alternate codewords having embedded data bits.
13. The system of Claim 12 further comprising:  
means for scanning the bitstream to locate blocks wherein the blocks contain the original codewords.
14. The system of Claim 12 wherein the bitstream has final codewords and further wherein the locations in the bitstream for embedding data into the bitstream correspond to the final codewords in the bitstream.

002401-01300

16. The system of Claim 12 wherein the codewords have a triplet form of EVENT = (RUN, LEVEL, LAST) and further wherein final codewords in the bitstream have a "LAST" coefficient = 1.

means for replacing final codewords in the bitstream with replaced codewords wherein the replaced codewords have a LAST coefficient = 0.

means for appending alternate codewords to the replaced codewords wherein the appended codewords = "0111s" wherein the "s" represents the embedded data bit.

19. The system of Claim 12 wherein the compressed bitstream corresponds to a compressed video bitstream.

**ABSTRACT OF THE DISCLOSURE**


The present invention is a method and system which extracts, manipulates and embeds data from a compressed and standard compliant video bitstream which may be used for digital rights management, e.g. controlling access to a bitstream or for authenticating a video bitstream.

The method embeds binary data bits into compressed and standard compliant video bitstream with minimal visual artifacts. The method first parses the compressed video bitstream and locates coded blocks. The codeword  $C$  for the last triplet in the original block ( $RUN_c, LEVEL_c, LAST_c = 1$ ) is replaced by the VLC code word  $C'$  for the last triplet ( $RUN_c, LEVEL_c, LAST_c' = 0$ ). A codeword corresponding to a triplet with  $LAST = 1$  is placed after  $C'$  whose sign bit "s" can be either 0 or 1 and is an embedded data bit, and can be used for authentication.

0037491.07E00

FIG - 1

Method of Embedding Data for Authentication Purposes





**DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**"METHOD AND SYSTEM FOR EMBEDDING BINARY DATA SEQUENCES INTO VIDEO  
BITSTREAMS"**

Case No. PVC-P-99-002 the specification of which

X is attached hereto,  
(check        was filed on                                 , as  
one) Application Serial No.                                   
and was amended on                                 .  
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent Office all information which is known to me to be material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, 1.56(a)<sup>1</sup>.

I do not know and do not believe this invention was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and I believe that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as identified below:

And I hereby appoint Brian M. Mattson (Reg. No. 35, 018) of the firm of Patents+TMS, A Professional Corporation, whose mailing address is 1914 North Milwaukee Avenue, Chicago, IL 60647, Tel. 773/772-6009; and Debra A. Chun (Reg. No. 38,700) of PacketVideo Corporation, as my attorneys/agents with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and direct that all

<sup>1</sup>(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

- (1) It establishes, by itself or in combination with other information, a *prima facie* case of unpatentability of a claim; or
- (2) It refutes, or is inconsistent with, a position the applicant takes in:
  - (i) Opposing an argument of unpatentability relied on by the Office, or
  - (ii) Asserting an argument of unpatentability.

A *prima facie* case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

002249-074200

